



5U 20-inch Deep RR Series Half Rack Shock Rack

SKU: 3RR-5U20-HR



Description

This standard commercial-off-the-shelf (COTS) case comes with a removable 1" deep front lid and 4" deep rear lid, as well as a built-in retractable pull handle, wheels, and 4 comfort grip spring loaded lift handles for maximum portability. The interior rack features SKB's patented "positive lock" latching system that slides open like a file drawer, allowing easy access to racked equipment. The rack can also be fully removed providing complete frame access for bench integration.

Like all 3RR Series Shock Racks, this half rack is molded of LMDP Linear Medium Density Polyethylene plastic that meets or exceeds MIL-STD 810H standards. It comes standard with 8 elastomeric shock absorbers which allow for a standard payload range of 40 to 150 lbs. The rugged roto molded shell and black powder coated stainless steel hardware (recessed for protection) ensure industry leading strength and impact resistance, while its compact size makes it highly portable and easy to deploy. Additionally, the molded-in stacking ribs and lugs are designed to stack with all SKB 3RR and 3RS shock racks—as well as competitive manufacturer's cases—making this the perfect complement to any collection of racked equipment.

Features

- 5U half-sized 9.5" width
- Standard rack depth 20" rail to rail
- Built-in wheels and telescoping pull handle for maximum portability
- Square hole rack rails to accommodate either #10-32 US standard or 6mm international standard cage nuts

- Removable lids, 1" deep front lid and 4" deep back lid
- Standard payload range of 40 to 150 lbs
- Completely removable frame for access to bench integration
- Meets or exceeds MIL-STD 810H
- Rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with all SKB 3RR and 3RS cases, as well as competitive manufacturer cases
- Recessed black powder coated stainless steel hardware
- Four (4) comfort grip spring loaded lift handles
- Automatic pressure relief valve (standard)

Specifications

Exterior	Hard	
Built In Wheels or Casters	Yes	
Product Weight	47.4 lb	21.50 kg
Exterior Length	33.5 in	85.09 cm
Exterior Width	14.5 in	36.83 cm
Exterior Height	17 in	43.18 cm
Carton Length	36 in	91.44 cm
Carton Width	18 in	45.72 cm
Carton Height	18 in	45.72 cm
Shipping Weight	54.2 lb	24.58 kg

AVAILABLE CONFIGURATIONS

3RR-5U20-HR	Black
-------------	-------