



Product specification sheet

Product title | 3RS-9U24-25B SKB Static Shock Rack 9U



Description

SKB's 3RS Shock Rack cases are tougher, lighter, stronger and better than any other rack case out there in the market. The 3RS series cases are identical to the 3RR series only with a static mounted shock rack instead of a removable rack. These cases are also featured-packed for ease of use, with convenient integrated wheels (24" and 30" models only), lid hangers, couplings straps, and more. All 3RS cases are independently tested and MILSTD 810-G certified. This means you can use our 3RS racks in the most extreme environments and conditions while your sensitive equipment will keep working and stays protected. And we are so convinced of the quality that we back it up with a lifetime warranty! These 24" deep rack models are suitable for IT equipment such as routers, switches, storage and communication devices. Typical applications are in military, security, and broadcast, where maximum protection is needed!

Features

- Meets or Exceeds MIL-STD 810G that means you are assured of performance & quality
- IP67 rating ensures your devices stay dry no matter what weather
- Standard shock absorbers suitable for payload range of 18 to 68 kg with extra shock absorber kits available to extended payload up to 136kg if added weight is needed
- Integrated side casters eliminate heavy lifting & ensure easy transport
- Roto-molded shell ensures industry leading strength & impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers cases
- Black powder coated stainless steel latches are recessed for protection & durability
- A built-in pressure relief valve helps to maintain an ideal environment at any altitude
- Never lose your lid again! the case housing has convenient lid hangers

Specifications

• Interior Length	61.0 cm	24.1 inch
• Interior Width	48.3 cm	19.1 inch
• Interior Height	40.0 cm	15.8 inch
• Base Depth	12.7 cm	5.0 inch
• Lid Depth	5.1 cm	2.1 inch
• Exterior Length	98.4 cm	38.8 inch
• Exterior Width	61.0 cm	24.1 inch
• Exterior Height	56.5 cm	22.3 inch
• Carton Length	102.3 cm	40.3 inch
• Carton Width	62.3 cm	24.6 inch
• Carton Depth	57.2 cm	22.6 inch
• Rack Depth	61.0 cm	24.1 inch
• Depth Front Rail to Rail	61.0 cm	24.1 inch
• Depth Front Rail to Back Lid	73.7 cm	29.1 inch
• Shipping Weight	37.2 kg	82.0 lb
• Product Weight	28.5 kg	62.8 lb
• Rack Units: 9		