

Product specification sheet

Product title

3SKB-R04U20W SKB 4U Industrial Shock Mount Rack







Description

The 1SKB 20? Rolling Shock Racks provide a great value option while not compromising on one key commitment: keeping your equipment safe! These 20? deep roto molded cases offer great protection with an internal frame mounted on adjustable elastomer shock absorbers on all eight corners, controlling the effects of shock and vibration on three axes. This design also makes for enough "sway" space around the internal frame for an optimized air circulation and heat dissipation?very important when your delicate equipment is mounted and running. With our 1SKB Rolling Shock Racks you also save big on weight versus traditional flight cases and wooden cases. The integrated wheels and pull handle make for easy lifting and transport. These models well accommodate audio mixers, video recording devices and communication equipment such as routers, switches, etc. Typical applications are in broadcast, music, pro audio, outdoor events and many more markets.

Features

- · Large recessed handles provide an easy & secure grasping point
- · Easy to mount your equipment with all necessary hardware included
- · Includes rear rack rails for even more secure mounting of your device
- · No more heavy lifting & carrying with integrated pull handle and wheels
- · Front & rear lid for easy & fast access!
- · Standard shock absorbers suitable for payload range of 18 to 68 kg
- · Need more weight? Optional shock absorber kit available to extended payload range from up to 136kg
- · Easy & secure transport or storage with integrated stacking ribs
- Lifetime warranty
- Available from 4U to 12U models

Specifications

50.8 c	cm	20.0 inch
48.3 c	cm	19.1 inch
17.8 c	cm	7.1 inch
5.7 c	cm	2.3 inch
5.7 c	cm	2.3 inch
73.3 c	cm	28.9 inch
71.8 c	cm	28.3 inch
41.0 c	cm	16.2 inch
75.0 c	cm	29.6 inch
73.0 c	cm	28.8 inch
42.0 c	cm	16.6 inch
50.8 c	cm	20.0 inch
50.8 c	cm	20.0 inch
56.5 c	cm	22.3 inch
21.2 k	кg	46.7 lb
18.7 k	кg	41.2 lb
	48.3 (17.8 (5.7 (5.7 (73.3 (71.8 (41.0 (75.0 (73.0 (42.0 (50.8 (50.8 (50.5 (21.2 (50.8 cm 48.3 cm 17.8 cm 5.7 cm 5.7 cm 73.3 cm 71.8 cm 41.0 cm 75.0 cm 73.0 cm 42.0 cm 50.8 cm 50.8 cm 51.2 kg 18.7 kg